

Netgear DM 602 NAT Router/Modem - Setup

Aim of this article:

This article provides a guide to configuring the Netgear DM 602 to connect.

NOTE: The DM 602 is a NAT Router/Modem which can be used to connect a single PC, or a network using a private IP range. It can not be used in a Routed IP mode.

Configuring the DM 602:

Begin by opening the DM 602's Web Configuration screen by entering the following address in your Web browser:

http://192.168.0.1

You will be prompted for a username and password, the defaults are as follows:

Username: **admin**

Password: **password**

Once you are logged in click on **Basic Router Settings**. This will bring up a page similar to the one shown below:

NETGEAR ADSL Modem DM602
settings

Setup
 • Basic Router Settings
Logout
Advanced
 • Router Status
 • LAN IP Setup
 • Set Password
 • Router Upgrade
 • Port Forwarding
 • DMZ
 • Device Mode

Basic Router Settings

Does Your Internet Connection Require A Login?
 Yes
 No

Encapsulation
 PPP over ATM

Login zen.j@zen
Password [redacted]
Idle Timeout 0

Domain Name Server (DNS) Address
 Get Automatically From ISP
 Use These DNS Servers
 Primary DNS [] . [] . [] . []
 Secondary DNS [] . [] . [] . []

ISP Parameters for Internet Access
 Multiplexing Method VC-BASED
 Virtual Circuit
 Rest of World UK user enter
 VPI 0 (0~255)
 VCI 38 (1~65535)

Apply Cancel Test

The settings on this screen should be as follows:

Does your Internet Connection Require A Login: **Yes**

Encapsulation: **PPP over ATM**

Login: This should be the username provided in your **Technical Details** e-mail. This is case sensitive.

Password: This should be the password provided in your **Technical Details** e-mail. This is case sensitive.

Idle Timeout: **0**

Domain Name Server (DNS) Address: **Get Automatically from ISP**

Multiplexing Method: **VC-BASED**

Virtual Circuit: **UK**

VPI: **0**

VCI: **38**

Once these settings are entered click **Apply**.

The settings should now be saved and the Router will establish the Internet connection after around one minute.